



**WATERWAYS PRODUCTS (AUST) PTY LTD**

**STT17 SEMI-AUTOMATIC SOFTENER**

Semi-automatic  
twist timer regeneration

Sand Stone  
Colour co-  
ordinated



Brass fittings - Semi automatic timer



Fibreglass (Resin Transfer Moulded)  
Cabinet and matching lid

Type	Semi automatic twist timer cabinet model water softener
Description	Colonial white one piece hand laid fibreglass cabinet with styled lid. Salt & brine storage within the cabinet
Capacity	17,000 litres at 100 mg/l (ppm) water hardness
Resin Volume	28 litres of high grade softening resin
Control Valve	Erie 3 stage with integrated twist time activated regeneration. Brass mains connection fittings. Adjustable brine draw
Brine Valve	Shurz type positive action shut off with air check
Brine Depth	Approximately 35-40 cms measured from the bottom of the cabinet to the centre of the brine float when valve is in the closed (up) position
Pressure Vessel	Park USA thermowound fibreglass with blow moulded seamless liner. Vessel size 10" (25cms) x 35" (89cms)
Flow Rate	Maximum 30-35 litres per minute
Pressure Rating	Maximum operating pressure - 600 kpa (85 psi) Minimum operating pressure - 175 kpa (25 psi)
Pipe Connections	15 mm (1/2") inlet/ outlet
Salt Storage	50 kgs salt storage capacity
Salt Usage	Approximately 4.5 kgs per regeneration
Dimensions	995 mm high x 450 mm wide x 320 mm deep Height of inlet/ outlet pipe centres 930 mm from base of cabinet
Weight	44 kgs (dry)