



WATERWAYS PRODUCTS (AUST) PTY LTD

STT8 SEMI-AUTOMATIC SOFTENER

Semi-automatic
twist timer regeneration

Sand Stone
Colour co-ordinated



Brass fittings - Semi automatic timer



Fibreglass (Resin Transfer Moulded)
Cabinet and matching lid

Type	Semi automatic twist timer cabinet model water softener
Description	Colonial white one piece hand laid fibreglass cabinet with styled lid. Salt and brine storage within cabinet
Capacity	10,000 litres at 100 mg/l (ppm) water hardness
Resin Volume	18 litres of high grade softening resin
Control Valve	Erie 3 stage with integrated twist timer activated regeneration. Brass mains connection fittings. Adjustable brine draw
Brine Valve	Shurz type positive action shut off with air check
Pressure Vessel	Park USA thermowound fibreglass with blow moulded seamless liner. Vessel size 8" (20cms) x 35" (89cms)
Flow Rate	Maximum 20-25 litres per minute
Pressure Rating	Maximum operating pressure - 600 kpa (85 psi) Minimum operating pressure - 175 kpa (25 psi)
Pipe Connections	15 mm (1/2") inlet/ outlet and drain
Salt Storage	50 kgs salt storage capacity
Salt Usage	Approximately 3.0 kgs per regeneration
Dimensions	890 mm high x 450 mm wide x 320 mm deep Height of inlet/ outlet centres – 795 mm from base of cabinet
Weight	32 kgs (dry)