



WATERWAYS PRODUCTS (AUST) PTY LTD

SEV17 VOLUMATIC SOFTENER

Microprocessor on demand automatic regeneration

Sand Stone Colour co-ordinated



Fibreglass (Resin Transfer Moulded) Cabinet and matching lid

Type	Fully automatic water softener, on demand volume based regeneration
Description	Colonial white one piece hand laid fibreglass cabinet with styled lid. Salt and brine storage within cabinet
Capacity	17,000 litres at 100 mg/l (ppm) water hardness
Resin Volume	28 litres of high grade softening resin
Control Valve	Fleck 5000SE microprocessor with 5 stage regeneration. All functions fully adjustable. Valve also controls brine refill. 240 volts operation
Brine Depth	Approximately 40 – 45 cms
Pressure Vessel	Park USA thermowound fibreglass with blow moulded seamless liner. Vessel size 10" (25cms) x 35" (89cms)
Flow Rate	Maximum 35 – 40 litres per minute
Pressure Rating	Maximum operating pressure - 600 kpa Minimum operating pressure - 175 kpa
Pipe Connections	20 mm (3/4") inlet/ outlet. 15 mm (1/2") drain
Salt Storage	50 kgs salt storage capacity
Dimensions	1100 mm high x 470 mm wide x 340 mm deep Height to inlet/ outlet pipe centres 930 mm from base of cabinet
Weight	47 kgs (dry)
Pipe Measurements	Height from base (ground) to the centre of inlet/ outlet 94cms